



Pre-Cut Sideview Mirror Signal Tint Overlays Installation Instructions 2019+ Ram Trucks (w/ LED Signals on Sideview Mirrors)

Vinyl will stick to any clean, smooth surface although before applying, you'll need to make sure that the surface is free of dirt, wax, grease, etc. Surface temperature should be between 60° and 80° F and should remain in that range for at least 12 hours after application.

Tools recommended for proper application: A heat gun or high-power hair dryer, a lint-free cloth or microfiber towel, degreaser or alcohol, water, a razor knife or exacto blade, and a hard card or squeegee.

Please note that our stickers and decals are 100% guaranteed against defects – We will not accept returns and offer refunds for decals or stickers for installation damage. The application process may be intimidating if you've never done it before, but if you read the instructions before attempting to apply the decal and again as you're doing it, this should be a fairly painless task. Large decals, however, should only be applied by those with vinyl decal application experience and should have a helper. Please also note that once the decals have adhered to the surface, you should take extra care when using pressure washers (or ice scrapers) as these can cause damage to the vinyl, however, our high quality 6 year vinyl is safe for use under windshield wipers.

Step 1: Dry fit and get situated. Before you do anything else, check to make sure they are correct and get yourself associated with where each piece will be applied by dry fitting them.

Before you begin, make sure that your light has been properly cleaned. We recommend using a 1 part alcohol/2 parts water solution with a drop or two of dish soap (or any other suitable cleaning solution) that you know isn't going to damage your light or the adhesive backing.

Step 2: Prepare the surface & surrounding area. Clean not only the light lens itself, but the area surrounding the mirror light lens, too. Because static electricity is created when the tint is removed from the liner, any dust and debris will be pulled onto the adhesive side of the tint. So, clean, clean and then clean again!

Step 3: Pssshhh, psssh, pssh. After you've cleaned with your degreaser, denatured alcohol, rinsed with water and dried everything, it's time to get the tint on... But first, hit the lens with a few shots of the alcohol/water/dish soap solution we mentioned previously in these instructions. Be careful not to overdo it though — too much of it will require a lot of heating and squeegeeing to remove excess liquid.

Step 4: Time for tint. If you've sprayed your lens with the slip-solution, peel the piece of tint from the paper backing and move it towards the area to be tinted, eyeballing the alignment of the tint piece that is being applied. With the solution on the lens, the tint piece (once laid onto the lens) should slide around and remain repositionable. Once the piece of tint is in place (and you're satisfied with how it looks, gently squeegee from the center out to the edges. You should see your solution working its way out and the adhesive will start taking over. If you get a wrinkle, simply lift the tint, straighten it out, and lay it again avoiding another crease. After the tint strip is in place, the beveled edges of the lens will need to be done. For this, you'll need your heat gun or hair dryer. Starting from either end, heat up the vinyl until you start to see the material warp. As soon as that happens, slowly and gently (using a felt covered squeegee **be careful, heat guns are HOT**), smooth the edges of the heated vinyl over the beveled edge of the lens. Repeat this as you work your way down the strip of tint until the whole piece is conformed around the lens.

Step 5: Repeat the above steps for the other side of the vehicle!

EBAY CUSTOMERS: PLEASE DON'T FORGET TO LEAVE POSITIVE FEEDBACK – I strive to make sure my customers receive the best transaction possible! If for any reason you're not "5-star-satisfied", please contact me immediately!

*Hey, thanks again for your business!
We really do appreciate it.*

Share a picture (*or two!*) of where you stuck your new KLEVR Grafix decal on our Facebook Page and receive a coupon for **20% OFF** your next order from our secure online web store!

“Like” us at [FB.com/KLEVRgrafix](https://www.facebook.com/KLEVRgrafix)

Check out our other products and shop with us through the following online outlets:

*[eBay.com/usr/klevrgrafix](https://www.ebay.com/usr/klevrgrafix)
<https://klevrgrafix.com/store>*

KLEVR **GRAFIX**
YOUR NORTHEAST OHIO DECAL & VINYL GRAPHICS SOLUTION.